

# Disable a repo

Feb 2021

## Introduction

---

repo files, in CentOS are located in `'/etc/yum.repo.d'`. These files hold information (URLs) about where repositories are for CentOS programs (tcpdump, htop, nload etc.)

Each repo has it's own file, [CentOS-Base.repo](#), [epel-release.repo](#) etc.

Occasionally we might want to ignore or remove a repo file, in this example there is a repo file called [cdrom.repo](#) that I need to ignore/delete.

---

To temporarily ignore a repo, we can use the following syntax:

```
sudo yum disablerepo=cdrom install yum-utils -y
```

This is two commands combined. [sudo yum install yum-utils -y](#) and [yum disablerepo=cdrom](#).

This allows us to install [yum-utils](#) while telling CentOS to ignore repositories listed in the [cdrom.repo](#) file.

---

If we wish to disable a repo permanently then we can use the following syntax:

```
sudo yum-config-manager --disable cdrom
```

This will tell [yum-config-manager](#) to disable the repo file [cdrom](#) (note we do not require the .repo extension)

For this to work the [yum-config-manager](#) must have been installed ([yum install yum-config-manager](#)).

---

From:  
<http://cameraangle.co.uk/> - WalkerWiki - [wiki.alanwalker.uk](http://wiki.alanwalker.uk)

Permanent link:  
[http://cameraangle.co.uk/doku.php?id=disable\\_a\\_repo](http://cameraangle.co.uk/doku.php?id=disable_a_repo)

Last update: 2023/03/09 22:35

