

# Route Command

The **route** command allows dynamic setting of a route from the command line, however using **route** without any parameters will show the currently configured routes.

## Raspbian

Raspbian Jessie on a Raspberry Pi 3 (LAN connected only, no wifi or bluetooth)

```
route
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
default	137.58.71.254	0.0.0.0	UG	202	0	0	eth0
137.58.68.0	*	255.255.252.0	U	202	0	0	eth0

Here we can see the default gateway is **137.58.71.254** on **eth 0**

## CentOS

CentOS 6.6 on a server with 6 network interfaces (only eth0 is physically connected).

```
route
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
192.168.5.0	*	255.255.255.0	U	0	0	0	eth4
192.168.4.0	*	255.255.255.0	U	0	0	0	eth2
192.168.4.0	*	255.255.255.0	U	0	0	0	eth3
192.168.3.0	*	255.255.255.0	U	0	0	0	eth1
192.168.27.0	*	255.255.255.0	U	0	0	0	eth0
link-local	*	255.255.0.0	U	1002	0	0	eth2
link-local	*	255.255.0.0	U	1003	0	0	eth3
link-local	*	255.255.0.0	U	1004	0	0	eth4
link-local	*	255.255.0.0	U	1005	0	0	eth5
link-local	*	255.255.0.0	U	1006	0	0	eth0
link-local	*	255.255.0.0	U	1007	0	0	eth1
default	192.168.27.254	0.0.0.0	UG	0	0	0	eth0

Here we can see the default gateway is **192.168.27.254** on **eth0**

From:

<http://cameraangle.co.uk/> - WalkerWiki - [wiki.alanwalker.uk](http://wiki.alanwalker.uk)

Permanent link:

[http://cameraangle.co.uk/doku.php?id=route\\_command&rev=1474377775](http://cameraangle.co.uk/doku.php?id=route_command&rev=1474377775)

Last update: **2023/03/09 22:35**

