

Configure IP Address

In CentOS 6x the IP settings are held in file(s) located in the **/etc/sysconfig/network-interfaces** directory, there is one file for each physical interface, they are generally called:

ifcfg-eth0
ifcfg-eth1
ifcfg-eth2
ifcfg-eth3
ifcfg-eth4
ifcfg-eth5
ifcfg-lo

To see exactly what files you have, and what they are called simply do a list
ls /etc/sysconfig/network-scripts

To edit a file enter:

vi /etc/sysconfig/network-scripts/ifcfg-eth(0) — (use the correct eth number for your system)

Below is an example of a static ip configuration for the first NIC (ifcfg-eth0)

```
DEVICE="eth0"  
BOOTPROTO=none  
IPV6INIT=no  
NM_CONTROLLED=no  
ONBOOT="yes"  
TYPE="Ethernet"  
IPADDR=192.168.27.110  
NETMASK=255.255.255.0  
GATEWAY=192.168.27.254  
PERSISTENT_DHCLIENT=yes
```

From:

<http://cameraangle.co.uk/> - WalkerWiki - wiki.alanwalker.uk

Permanent link:

http://cameraangle.co.uk/doku.php?id=wiki:configure_ip_address&rev=1469299751

Last update: **2023/03/09 22:35**

